


External position sensor for Types 3730-2, -3, -4, -5 and -6 Positioners



Rugged and Reliable

- Easy attachment to linear and rotary actuators
- Compact, rugged design, degree of protection IP 67
- Immune to vibrations up to 10 g between 10 and 2000 Hz
- Also suitable for hazardous areas
- Temperature stability: -40 to 90 °C



External position sensor for Types 3730-2, -3, -4, -5 and -6 Positioners

- Position sensor and positioner in separate housings
- Position sensor mounted directly onto the valve
- Positioner can be installed away from the valve, e.g. on a wall
- Connecting cables and air ducts used to connect the controlled variable x and output variable y to the valve

Travel, angle of rotation	Linear actuators: 3.6 to 200 mm Rotary actuators: 24 to 100°
Immunity to vibration	Vibrations up to 10 g in the range between 10 and 2000 Hz
Degree of protection	IP 67
Permissible ambient temperature	-40 to 90 °C
Explosion protection	Ex ia Ex nL/nA
Cable	Ready-assembled connecting cable 10 m long, M12 connector



SAMSON AKTIENGESELLSCHAFT
Weismuellerstraße 3 · 60314 Frankfurt am Main, Germany
Phone: +49 69 4009-0 · Fax: +49 69 4009-1507
E-mail: samson@samson.de · Internet: www.samson.de